



Equiassiste®



Empresa Certificada



www.equiassiste.pt

Consumíveis - Solda por fio contínuo

Bobines de fio



Adaptador para bobine (5Kg - Ø200)



Bobine ecológica

Adaptador bobine ecológica



2 Fechos

Intensivo



100mm



0,9



0,6



0,8



0,8



0,8

	kg	100mm	200mm	300mm	Ø 0,6 mm	Ø 0,8 mm	Ø 1,0 mm	Ø 1,2 mm
Acer - Steel - Stahl - Acero - Staal - Aço (SG2)	0,9	100 mm	—	—	086593	086609	—	—
	5	200 mm	—	—	086111	086128	086135	—
	15	300 mm	—	—	086166	086227	086234	086241
	18	—	300 mm	—	—	086272	086289	086296
Galva (SGTI)	5	200 mm	—	—	086760	086777	—	—
Alu (AlMg5)	0,5	100 mm	—	—	—	086548	—	—
	2	200 mm	—	—	—	086555	086562	—
	7	300 mm	—	—	—	—	086524	086531
Alu (AlSi5)	0,5	100 mm	—	—	—	086685	—	—
	2	200 mm	—	—	—	—	086142	086159
Alu (AlSi12)	0,5	100 mm	—	—	—	086678	—	—
	2	200 mm	—	—	—	—	086067	086074
Inox - Stainless - Edelstahl (308LSI)	1	100 mm	—	—	—	086616	—	—
	5	200 mm	—	—	—	086579	—	—
Inox - Stainless - Edelstahl (316LSI)	5	200 mm	—	—	—	086326	—	—
	—	—	—	—	—	—	—	—
Cusi3 HLE - UHTS (Boron Steel)	1	100 mm	—	—	—	086692	—	—
	5	200 mm	—	—	—	086647	086654	—
CuAl8 HLE - UHTS (Boron Steel)	5	200 mm	—	—	—	086661	—	—
	—	—	—	—	—	—	—	—
Fil fourré, Cored wire, Fülldraht, Hilo tubular Acier - Steel - Stahl NO GAS	4,5	200 mm	—	—	—	—	Ø 0,9 = 086623	086630
	0,9	100 mm	—	—	—	—	Ø 0,9 = 086104	—
Rechargement Acier 60 HRS	16	—	300 mm	—	—	—	—	086173

NORMAS

DIN	AWS	EN
DIN 8559 : SG2	AWS 5.18 : ER 70S-6	EN ISO 14341-A : G42 2M G3Si1
DIN 8559 : SG2	AWS 5.18 : ER 70S-2	EN ISO 14341-A : G42 2M G2Ti
DIN 1732 : SG-AlMg5	AWS 5.10 : ER 5356	EN ISO 18273 : AlMg5
DIN 1732 : SG-AlSi5	AWS 5.10 : ER 4043	EN ISO 18273 : AlSi5
DIN 1732 : SG-AlSi12	AWS 5.10 : ER 4047	EN ISO 18273 : AlSi12
DIN 8556 : SG X2 CrNi 19 9	AWS 5.9 : ER 308L Si	EN ISO 14343-A : G19 9 L Si
DIN 8556 : SG X2 CrNiMo 19 12	AWS 5.9 : ER 316L Si	EN ISO 14343-A : G19 12 3 L Si
—	AWS 5.7 : ER CuSi-A	EN ISO 24373-A : S Cu 6560
—	AWS 5.7 : ER CuAl-A1	EN ISO 24373-A : S Cu 6100
—	AWS 5.20 : E71T-G5	EN ISO 17632-A : T42 Z WN 1 H15
—	—	EN 14700 : T7 Fe 2

Roletes



TYPE A



TYPE B



TYPE C



Pearl, Multippearl, Smartmig 110, 142, 162, 3P

Smartmig 182, 183, Monogys, Trimg, Pearl XL, TF 4R, GYS Auto

Magys, Neopulse, WS 4L, WS 4R

	Ø 0,6 / 0,8	Ø 0,8 / 1,0	Ø 1,0 / 1,2	Ø 1,2 / 1,4	Ø 1,2 / 1,6	Ø 0,8 / 1,0	Ø 1,0 / 1,2	Ø 1,2 / 1,6	Ø 0,9 / 1,2	Ø 1,6 / 2,4
Acier - Steel - Stahl - Acero - Staal - Aço Inox - Stainless	(x1) 042339	(x1) 041189								
						(x1) 041196	(x1) 042155	(x2) 042384	(x2) 041752	
						(x1) 042186	(x2) 040915	(x2) 042391	(x2) 042124	
							(x1) 042131	(x2) 042407	(x2) 042124	(x4) 040519
Alu										
Fil fourré - Corred wire										

Fil fourré - Corred wire Ø 0,9 Smartmig 110 (Ø 25 mm) (x1) 044081

Alicate especial para MIG-MAG



SUPORTE PARA TOCHA

MAGNÉTICO

041653


PROTECTOR EM SPRAY (SEM SILICONE)



041806

Kit soldadura NO Gas Ø 0,9

OEM : Universal 3P, Monomig 160-1, Pearl, Smartmig




M6-00,9 (x3)

Isolated Nozzle No Gas - 150 A (x1)

Ø 0,9 / 1,2 (x1)

Estojos

MB 15 (150 A) 041226



MB 25 (250 A) 041233



MB 36 (350 A) 041417



Equiassiste - Técnicas e Equipamentos para Oficinas Auto, Ida

Rua do Lameiro 559 - Oliveira do Douro - 4430-444 V.N.Gaia Tel:227 877 150 Fax:227 877 160

www.equiassiste.pt - equiassiste@mail.telepac.pt